


# DOOR STOP 5001

#### **DESIGNED BY BUSK + HERTZOG**

## PRODUCT DETAILS, TECHNICAL DETAILS AND FITTING INSTRUCTIONS



## MATERIALS: STAINLESS STEEL / BLACK RUBBER **AVAILABLE IN THE NINE FROST FINISHES:**

























BRUSHED STAINLESS

POLISHED STAINLESS BRUSHED COPPER POLISHED COPPER

BRUSHED GOLD

POLISHED GOLD

BRUSHED BLACK

A5001BLS MATT BLACK

A5001WS MATT WHITE




### **MOUNTING**

Place the Door Stop in the desired position and mark the screw holes with a cc distance of 30 mm.

The Door Stop can be mounted on either the wall or the floor.

Drill the marked holes using a 6 mm drill bit and insert the enclosed Ø6x30 mm wall plugs (A).






Secure the Door Stop with the enclosed Ø4x40 mm screws (a) and use a Phillips screwdriver with bit PH2 to tighten the screws.



Press the two rubber screw covers © into the screw holes, until they align with the surface.



#### CLEANING AND MAINTENANCE

Surfaces should be cleaned with a microfiber cloth, glass cleaner or other non abrasive and gentle agents.

#### ATTENTION:

Never use solvents or aggressive household cleaners like bleach, acids (e.g. descalers) or ammonia-based bathroom cleaner to clean the product. Steel wool and hard brushes can permanently damage the surface of the steel.

#### **EXCLUSION OF LIABILITY**

FROST accepts no liability whatsoever for damage to persons or property that occurs or has occurred as a result of improper installation or maintenance, particularly if the safety instructions and other points to note listed are not or have not been observed in full.

#### WARNING AND HAZARD NOTICES

Improper mounting or use can lead to accidents and serious injuries.

#### www.frostdenmark.com

Bavne Alle 32, 8370 Hadsten, Denmark E-mail: info@frost.dk • Phone: (+45) 87 61 00 32

We are also to be found as frostdenmark on Facebook, Instagram, Pinterest and LinkedIn







